



INTUITIONLABS / RESEARCH & PRACTICAL GUIDANCE

Token Optimization and Cost Management for ChatGPT & Claude

Build practical AI for pharma and biotech with IntuitionLabs. We help life-science teams turn complex information and workflows into useful software, governed knowledge systems and AI tools.

Published by IntuitionLabs · 2026-04-12 · token optimization · chatgpt · claude · llm costs · context windows · prompt engineering · token usage patterns · api pricing

Original article: <https://intuitionlabs.ai/articles/token-optimization-chatgpt-claude-costs>



In this article

1. Executive Summary
 2. Introduction and Background
 3. 1. Token Fundamentals and Model Context
 4. 1.1 What Is a Token?
 5. 1.2 Context Window and the "Hidden Tax"
 6. 1.3 Pricing and Token Costs
 7. 1.4 Token Counting in Practice
 8. 2. ChatGPT Token Usage Patterns
 9. 2.1 ChatGPT Overview
 10. 3. Claude Token Usage Patterns
 11. 3.1 Claude Overview
 12. 3.6 Usage Caps and Policy
 13. 4. Comparing ChatGPT and Claude Tokenization and Costs
 14. 4.1 Tokenization Differences
 15. 4.2 Pricing and Cost Structure
 16. 4.3 Context Windows and Long-Form Use
 17. 5. Token Optimization Techniques
 18. 5.1 Prompt Formulation and Compression
 19. 5.2 Context Management
 20. 5.3 System-Level and Workflow Strategies
 21. 5.4 Case Study Highlights
 22. 6. Data Analysis and Examples
 23. 6.1 Quantifying Progressive Costs
 24. 6.2 ChatGPT Usage Statistics
 25. 6.3 Case Example: System Prompt Overhead
 26. 6.4 Branch8 Team Example
 27. 7. Case Studies and Real-World Examples
 28. 8. Implications and Future Directions
 29. 8.1 Larger Contexts – Double-Edged Sword
 30. 8.2 Pricing and Market Dynamics
 31. 8.3 Open-Source and Local Innovation
 32. 8.4 Token-Efficient Prompting Research
 33. 8.5 Ethical and User-Experience Considerations
 34. 9. Conclusion
-

Executive Summary

In recent years, usage of advanced conversational AI systems like OpenAI's **ChatGPT** and Anthropic's **Claude** has exploded, highlighting the critical importance of efficient token management. Each query or message to these large language models (LLMs) is broken down into *tokens* – subword units that drive computation and cost. Mismanaging token usage can dramatically inflate response costs, degrade performance, and exhaust model context windows (medium.com) (www.geeky-gadgets.com). For example, studies show that repeatedly continuing a long conversation causes token costs to skyrocket (the so-called “*hidden token tax*”), such that a simple three-word user input cost USD \$0.0018 on message 1 and \$2.41 by message 260 in one Claude session (medium.com). Similarly, OpenAI notes that even trivial courteous replies (“thank you”/“please”) can cumulatively cost “tens of millions of dollars” in compute (www.tomshardware.com). Thus, optimizing token usage is no longer a micro-optimization but a business-critical concern for AI applications.

This report provides a comprehensive analysis of **token usage patterns** and **optimization techniques** for ChatGPT and Claude. It first reviews the background of tokens and context windows in transformer-based LLMs, including how **prompt caching reuses shared-prefix work**. Next, it examines typical usage patterns for ChatGPT and Claude, contrasting their tokenization schemes, pricing models, and user behaviors. Numerous data-driven insights are presented: for example, OpenAI models measured on OpenRouter processed ~78.3 billion tokens in a single day during the 2025 school season (www.techradar.com), and Claude Code costs vary with model choice, codebase size and usage patterns ([Anthropic documentation](#)). The report distinguishes cumulative retained input from computation and billed cost. Concessao's token-overhead observations come from 300 messages in one Claude session, rather than a representative sample of ChatGPT and Claude users ([primary account](#)).

The report then delves deeply into **optimization strategies**. It covers general prompt-engineering tactics (concise phrasing, context limitation, semantic chunking) (medium.com), and tools/commands specific to Claude Code (e.g. `/clear` and `/compact`) for managing context. A `.claudeignore` file has no effect ([permissions documentation](#)). Examples illustrate these techniques: IBM Developer assigns a sample prompt 25 instruction tokens ([IBM Developer](#)); evaluate actual usage and answer quality before treating its examples as end-to-end savings, and an engineer's restructuring of Claude Code projects reduced token use by 70% (harikayenuga.medium.com). A detailed table (below) contrasts original vs. optimized prompts with corresponding token counts and costs.

Finally, the report discusses broader implications and future trends. As context windows expand (GPT-4o at 128K tokens (gptbreeze.io) and Claude Opus 4.6 and Sonnet 4.6 offering 1M context at standard pricing on the Claude Platform ([Anthropic](#))), the hidden token tax will persist unless architectural changes are made. Emerging solutions include prompt compression research (e.g. generative summarization of prompts (arxiv.org)), more efficient memory architectures, and reliance on retrieval/memoization to avoid redundant tokens. We also review how model pricing shifts (e.g. Anthropic ending “unlimited” plans (www.madrona.com)) are forcing even more disciplined token usage. In sum, by carefully crafting prompts, managing context, and choosing appropriate models, developers can dramatically improve both **cost-efficiency** and **performance** of ChatGPT/Claude systems — a necessity as these tools become ubiquitous in industry and academia.

Introduction and Background

Large Language Models (LLMs) such as OpenAI's ChatGPT (based on the GPT series) and Anthropic's Claude have transformed human-computer interaction. These models are built on the *transformer* architecture, which processes input as a long sequence of *tokens* – subword text units typically smaller than words ([medium.com](#)). For example, the word “tokenization” may be broken into tokens like “token”, “##ization” by a BPE (byte-pair encoding) tokenizer ([medium.com](#)). Each query and response exchanged with an LLM is counted in tokens, and importantly, *every token processed incurs computational cost*. Consequently, token usage patterns directly determine both performance and expense of using ChatGPT or Claude.

A model's **context window** defines the maximum number of tokens it can process in a single pass ([medium.com](#)). For early GPT models this was on the order of 2,048–4,096 tokens; modern versions support much larger contexts. For instance, GPT-4 historically had an 8,192-token limit (approximately 6,000 English words on average ([www.linkedin.com](#))), with a 32,768-token GPT-4-32k variant, and GPT-4 Turbo and GPT-4o later raising the limit to 128,000 tokens ([gptbreeze.io](#)). Claude's context window has also scaled: Claude Opus 4.6 and Sonnet 4.6 include the full 1,000,000-token window at standard pricing on the Claude Platform ([Anthropic](#)). In practical terms, larger context windows enable lengthy conversations or documents in a single session; however, they also mean that naive usage can accumulate extremely large token counts quickly.

Retaining conversation history can increase later input-token counts, but this does not mean every prefix is recomputed from scratch. OpenAI documents reuse of shared-prefix work through **prompt caching**, and **Anthropic supports prompt caching** for its active models. Claude Code also **automatically compacts conversations before the context window fills**. Distinguish cumulative input-text counts from computation and billed cost, as explained in Section 1.2.

This *hidden cost* becomes concrete when each token has monetary value. Both OpenAI and Anthropic charge (or incur) costs per input/output token. For example, as of late 2025, OpenAI's GPT-4o has input tokens at about **\$2.50 per 1,000,000 tokens** and output tokens at **\$10 per 1,000,000 tokens** ([gptbreeze.io](#)). Claude's enterprise models (Sonnet/Opus 4.6) charge roughly **\$3–\$5 per 1,000,000 input tokens** and **\$15–\$25 per 1,000,000 output tokens** ([www.madrona.com](#)). Even if a user is on a flat-rate plan (e.g. ChatGPT Plus at \$20/month or Claude Max at \$200/month), the underlying compute is real and subsidized by the companies behind them. Altman has said that users' polite phrases (“thank you”, “please”) have cost OpenAI “tens of millions of dollars” in compute ([www.tomshardware.com](#)). In aggregate, ChatGPT is estimated to cost OpenAI on the order of **\$17 billion per year** to operate globally ([www.techradar.com](#)) (well beyond user subscription revenues). Thus, understanding **token usage patterns** – how and why tokens are consumed – is pivotal for cost management and model performance.

Token usage is influenced by both **user behavior** and **system design**. On the user side, factors include prompt phrasing (verbosity, clarity), conversation length, and frequency of interactions. On the system side, factors include the model's built-in system prompts, safety completions, and any auxiliary tools integrated (e.g. web search, code execution) which each consume tokens ([medium.com](#)). Concessao tracked 300 messages in a single Claude session ([primary account](#)); that personal observation does not establish a typical human-

token percentage across ChatGPT and Claude. Inspect the actual session rather than assuming universal overhead, as discussed in Section 6.3. Caching can also reuse repeated prefix work ([OpenAI documentation](#)), so resetting a conversation is not the only way to address repeated-input costs.

In this report, we analyze both historical context and cutting-edge developments in token usage. We compare ChatGPT and Claude from multiple angles: **tokenization differences**, **context management**, **usage quotas**, and **pricing models**. We synthesize data from academic and industry sources, including usage analytics (e.g. OpenRouter reporting token totals for models used on its platform ([OpenRouter documentation](#)) ([www.techradar.com](#))) and corporate policies (e.g. Claude's dynamic 5-hour session limits ([www.techradar.com](#))). We then survey techniques for token optimization in real applications: from guiding users to phrase prompts more succinctly, to engineering developer workflows that leverage Claude Code's special commands ([harikayenuga.medium.com](#)) ([docs.anthropic.com](#)). Examples include IBM Developer's sample prompt figures ([IBM Developer](#)), which should be evaluated with measured usage and answer quality before claiming end-to-end savings, and restructuring an entire coding project's prompt strategy yielded a **72%** API cost reduction in practice ([branch8.com](#)). We further examine the **implications**: how emerging models with megaplex context windows (GPT-4o, Claude Opus 4.6) change the landscape, and what future R&D (e.g. prompt compression algorithms ([arxiv.org](#)) or more efficient memory architectures) may bring.

Throughout, all claims are backed by published evidence or technical documentation. The strategies discussed are supported by performance metrics, security whitepapers, and professional experience; detailed references are provided. By the end, the reader will have a deep understanding of *why* token efficiency matters, *how* to diagnose and analyze token consumption, and *what specific methods* yield the best improvements when using ChatGPT or Claude in any production setting.

1. Token Fundamentals and Model Context

1.1 What Is a Token?

A **token** is the atomic text unit used by an LLM's tokenizer. Different LLMs use slightly different schemes, but typically a token is either a word or a subword. OpenAI's models use a byte-pair encoding (BPE) tokenizer: common words will be one token, while rare or long words break into multiple tokens (e.g. "unhappiness" → "un", "##happy", "##ness") ([medium.com](#)). Similarly, Claude's tokenization (Anthropic has not publicly detailed their tokenizer, but tools confirm it is largely comparable) splits text at roughly the word/subword level. On average in English, about **4 tokens ≈ 3 words** for GPT models ([www.linkedin.com](#)). Thus, a 1,000-word essay is on the order of **1,300–1,400 tokens**. Table 1 illustrates typical conversions:

- GPT-3.5/GPT-4 average: 1 token ≈ 0.75 English word ([www.linkedin.com](#)).
- In practice: "Write an article about X" (6 tokens) yielding a 1,000-word output (~1,300 tokens) would consume ~1,306 tokens ([www.linkedin.com](#)).

Because every model input and output is measured in tokens, this directly ties to model cost and speed. Larger token counts mean more computation (quadratically more in the attention layers) and thus slower inference and higher cloud costs ([medium.com](#)).

1.2 Context Window and the “Hidden Tax”

Conversation history can contribute input tokens on later turns, but repeated input does not necessarily require all prefix computation to be repeated. OpenAI documents prompt caching for shared prefixes, and Anthropic documents resuming from cached prompt prefixes ([OpenAI](#); [Anthropic](#)).

As a simplified cumulative input-token example, suppose request k contains k equal-sized units of retained text, with no trimming or compaction. Across n requests, the sum is $T(n)=1+2+\dots+n=n(n+1)/2$. At $n=50$, that is 1,275 units, or 25.5 times the 50 units in 50 independent one-unit inputs ([Concessao](#)). This arithmetic counts repeated input text under those assumptions; it is not a formula for prefill computation, attention complexity, or the bill.

Caching can reuse work on eligible prefixes, while compaction can shorten the retained history. Claude Code automatically compacts conversations before its context window fills ([Claude Code best practices](#)). Evaluate those mechanisms before recommending a reset solely to reduce cost.

1.3 Pricing and Token Costs

Both OpenAI and Anthropic expose token-based pricing (in APIs or indirectly in subscriptions). For concreteness, typical cost figures (as of 2026) are:

- **OpenAI ChatGPT/GPT:** Recent GPT-4-class models cost on the order of \$2–\$3 per million input tokens and \$8–\$10 per million output tokens. For example, GPT-4.1 (with a context window of about 1M tokens) is ~\$2 per 1M input tokens and \$8 per 1M output ([platform.openai.com](#)). The new GPT-4o (128K context) is roughly \$2.50 per 1M input and \$10 per 1M output ([gptbreeze.io](#)) (Table 1). GPT-3.5 Turbo was cheaper still (fractions of a cent per thousand tokens). ChatGPT’s free and Plus subscription tiers abstract these costs from end-users, but corporate customers on the API pay per token.
- **Claude (Anthropic):** Claude’s API pricing (April 2026) for its models is similar in scale. The high-end enterprise Claude Opus 4.6 charges about **\$5 per million input tokens** and **\$25 per million output tokens** ([www.madrone.com](#)) (i.e. \$0.005 and \$0.025 per thousand tokens). The mid-tier Claude Sonnet 4.6 is \$3 per million input and \$15 per million output ([www.madrone.com](#)). The cheaper Claude Haiku 4.5 is \$1/\$5 per million, intended for simplest tasks. In comparison, OpenAI’s GPT-4o at \$10 per million output equates to \$0.01 per thousand tokens, roughly similar to Claude Sonnet’s \$0.015 per thousand output tokens. These are summarized below.

Model	Input Cost	Output Cost	Max Context	Sources
GPT-4.1 (OpenAI)	\$2 per 1M (≈\$0.002/1K tokens)	\$8 per 1M (≈\$0.008/1K tokens)	≈1,000,000 tokens (the original GPT-4 had 8,192 tokens, ~6k words) (www.linkedin.com)	OpenAI pricing
GPT-4o (OpenAI)	\$2.50 per 1M (≈\$0.0025/1K tokens)	\$10 per 1M (≈\$0.010/1K tokens)	128,000 tokens (gptbreeze.io)	OpenAI pricing

Model	Input Cost	Output Cost	Max Context	Sources
Claude Sonnet 4.6	\$3 per 1M (≈\$0.003/1K tokens)	\$15 per 1M (≈\$0.015/1K tokens)	1,000,000 tokens on the Claude Platform, generally available at standard pricing since March 13, 2026	Anthropic
Claude Opus 4.6	\$5 per 1M (≈\$0.005/1K tokens)	\$25 per 1M (≈\$0.025/1K tokens)	1,000,000 tokens on the Claude Platform, generally available at standard pricing since March 13, 2026	Anthropic

Table 1. Comparison of API token pricing and context limits for OpenAI and Anthropic model examples. The GPT-4.1 and GPT-4o rows are API examples; those models retired from ChatGPT in February 2026 ([OpenAI retirement notice](#)). Input/output costs are given per 1,000,000 tokens.

In consumer settings, distinguish ChatGPT subscription allowances from API token billing: API usage is separate and billed independently ([OpenAI Help Center](#)). Consult each plan's current allowances when budgeting subscription use. However, heavy users on those plans often greatly exceed their “internal” system cost. Madrona reports one developer used ~10 billion tokens in 8 months with Claude Max; at list API pricing that would be ~\$15,000 in input tokens (the plan cost only \$800) ([www.madrona.com](#)). Growth in AI usage has prompted changes: Anthropic, for instance, recently dropped legacy “flat-rate” channels (such as Third-party wrappers that pour usage through subscriptions) and now charges “true” per-token bills for extra use ([www.madrona.com](#)). Thus, both Free and paid tiers of ChatGPT/Claude carry *implicit* token economics that increasingly align with their per-token API pricing as usage becomes heavy ([www.madrona.com](#)).

1.4 Token Counting in Practice

Developers commonly use token counting tools to audit prompt length. For example, OpenAI provides APIs that return the exact input and output token count for each request. In Claude Code (Anthropic's coding assistant), one can run `/cost` to get a summary of tokens used in a session ([docs.anthropic.com](#)). Monitoring tools like Kontinuity or Branch8's scripts can parse session logs to tally tokens. These allow empirical analysis of usage patterns. For instance, Branch8 reported auditing session logs for a distributed team and finding obscene waste of context tokens: teams would optimize 200-token system prompts while ignoring their 80,000-token conversation histories ([branch8.com](#)) – an order-of-magnitude mismatch in optimization focus.

IBM Developer assigns a sample prompt 25 instruction tokens and a cost of \$0.025 ([IBM Developer](#)), implying an illustrative \$0.001 per instruction token. Treat Table 2 as an instruction-text illustration; measure end-to-end usage and latency in the intended workload before claiming savings. Similarly, in Claude Code, Yenuga measured 200K tokens consumed in just 20 minutes of debugging ([harikayenuga.medium.com](#)) – far beyond what a human user might estimate, underscoring the need for vigilance in tracking.

In summary, tokens are the fundamental currency of these AI systems. Every feature – context length, conversation design, prompt structure – revolves around tokens. Optimization thus begins with understanding and measuring token usage in one's workflows. The sections that follow will dive into ChatGPT-specific and Claude-specific usage patterns, and detail proven ways to optimize them.

2. ChatGPT Token Usage Patterns

2.1 ChatGPT Overview

OpenAI's ChatGPT (with model access depending on the plan and workspace settings; see [OpenAI's current model guide](#)) has become one of the most widely adopted AI tools. It is used for chat assistants, content creation, coding help, tutoring, and more. As such, usage spans casual Q&A to intensive developer workflows. Key characteristics relevant to tokens include:

- **Context Maintenance:** ChatGPT's conversation structure persists context across turns until it is reset. Each new user message includes the entire prior chat. Users can often scroll up to see previous text. Unlike Claude Code (which can explicitly clear or compact), ChatGPT requires starting a *new chat* to obtain a fresh context.
- **System and Assistant Prompts:** Every conversation has a hidden system prompt that shapes the assistant's behavior (e.g. "You are ChatGPT, a helpful AI..."). OpenAI does not reveal the entire prompt publicly, but it can be thousands of tokens long ([medium.com](#)). In the OpenAI API, [prompt caching](#) can reuse work on shared prefixes, so repeated input does not necessarily require repeated computation.
- **Usage Tiers:** ChatGPT's free tier has a daily message cap, while Plus (and higher) have larger caps. Enterprise customers use the API with explicit token quotas. The flexible tiers mean power users often seek to minimize tokens per session to stretch usage.
- **Token-Cost Awareness:** Most consumer users don't directly see token counts. Developers using the API can easily see it. However, trends like inserting "please" can legally add a token cost. Altman's comment on "thank you" shows that even users' politeness registers as token consumption (and water usage!) on the backend ([www.tomshardware.com](#)).

Despite some opacity, certain usage patterns are well known:

2.2 Typical ChatGPT Conversation Patterns

OpenRouter's daily-token dataset reports total token usage for models accessed through OpenRouter ([primary documentation](#)). These totals describe that platform's routed model traffic; they do not establish ChatGPT-app usage or classroom activity. Use evidence specific to the ChatGPT product before drawing conclusions about its users or academic-season patterns.

In practice, smaller-scale users also exhibit patterns that affect tokens:

- **Redundancy in Conversation:** Without realizing it, users may repeat context or confirm details. For instance, instead of simply continuing a question, they might re-paste or reword prior info, thinking the model forgot (even though it hasn't). Each repetition costs extra tokens that could have been avoided.
- **Politeness and Fillers:** Many users write messages as if talking to a person, e.g. "Hello ChatGPT, could you please... thank you!" Every "please" and "thank you" is an extra token (e.g. "please" = 1 token). Altman notes OpenAI pays for these – every reply, even "you're welcome", uses a small but nonzero amount of compute ([www.tomshardware.com](#)).

- **Excess Detail in Prompts:** Users sometimes provide long instructions or data sets in the prompt. For example, dumping the full text of a PDF or website into ChatGPT can consume hundreds of tokens upfront. While context can help, often much of it is irrelevant and could be compressed or summarized.
- **Keeping Chats Too Long:** Users may not restart chats when switching topics. A support conversation might be kept alive even after resolution. This causes “context drift” – old information lingers in memory, bloating token count for no benefit. Geeky Gadgets warns that one common ChatGPT habit is letting threads extend indefinitely, and recommends resetting every ~10–15 turns to curtail wasted context (www.geeky-gadgets.com).

2.3 Evidence of Token Waste and Hidden Costs

Several analyses confirm that many ChatGPT users inadvertently waste tokens:

- **Progressive Input Growth:** Retaining a growing history can increase cumulative input-token counts. It does not follow that every prefix is recomputed from scratch: supported OpenAI models can reuse shared-prefix work through prompt caching ([OpenAI](https://openai.com/blog/prompt-caching)). Assess cache reuse and context management before recommending a new chat solely on cost grounds.
- **Empirical Monitoring:** Commercial tools (like prompt optimizers) and open-source scripts often show a high percentage of tokens attributed to preamble text and history, not the user’s current input. One developer’s analysis found that by the 206th message, the user’s message of 1,581 tokens was only ~1.3% of the ~118k tokens the model processed (medium.com).
- **Usage Quotas and Limits:** ChatGPT’s own service imposes usage limits per day, which implicitly caps tokens. Anecdotally, users on free tiers hit limits more quickly when they chat without resetting, for the reasons above. While OpenAI doesn’t always publish hard token limits, the existence of daily message caps indicates the underlying token usage is a factor.

2.4 Cost Implications

For organizations or individuals paying token costs, even small inefficiencies add up. As Branch8 reports, naive workflows had a 6-person team burning USD \$2,400 in their first month of Claude usage (analogous to ChatGPT API usage) (branch8.com). ChatGPT API customers see similar patterns: a prompt that is a few hundred tokens longer will cost appreciably more (e.g. a 300-token prompt vs. 100-token prompt at GPT-4’s rates is \$0.009 vs \$0.003 input cost at the original GPT-4’s \$30 per million input tokens).

On the consumer side, OpenAI has begun to explicitly monetize tokens. For example, ChatGPT now shows message counters for free users, and there are premium plans with higher token allowances. The recognition that “free” ChatGPT has real costs (www.techradar.com) has led OpenAI to cap free usage and offer paid alternatives. Each Free tier message may seem free to the user, but collectively they drive OpenAI’s massive expenses: techradar estimates ~\$17B/yr to serve ChatGPT worldwide (www.techradar.com). Thus, even from OpenAI’s perspective, reducing superfluous token traffic is vital for sustainability.

In summary, **ChatGPT token usage patterns** are characterized by multi-turn dialogues, repetitious context, and high volume under heavy adoption. These patterns often incur hidden quadratic costs in tokens. Awareness of how ChatGPT accumulates tokens is the first step toward mitigation. In the next section, we examine similar patterns in Claude and then dive into concrete optimizations for both.

3. Claude Token Usage Patterns

3.1 Claude Overview

Anthropic's **Claude** is a series of conversational LLMs (Claude Instant 1.0, Claude 2, Claude Opus 4.x, Claude Sonnet 4.x, etc.) designed with a particular emphasis on safety and assistance. Like ChatGPT, Claude is sold via web/chat interfaces (Anthropic has Pro/Max subscriptions) and via APIs for developers. However, several aspects of Claude's design and ecosystem affect token usage:

- **Usage Windows:** On Claude Max, the session-based usage allowance resets every five hours ([Claude Max documentation](#)). A usage-window reset should not be treated as a command to clear or discard a conversation.
- **Tokenization:** Claude's tokenization is analogous to ChatGPT's (subword-based). As with GPT, common words may be one token ("dog"), but compound terms may split ("credit-card" → "credit", "-", "card"). Anecdotal comparisons suggest that Claude token usage is in the same ballpark as GPT for typical prompts, although exact distributions can differ slightly.
- **Internal Leadership:** Anthropic often emphasizes "*constitutional AI*" and roles embedded in system prompts, so Claude's system messages tend to be lengthy (potentially thousands of tokens of guidelines) ([medium.com](#)). This means the "hidden tax" of system tokens may be even larger proportionally in Claude.
- **Use Cases:** Claude is popular not only for casual chat but also for *agentic/code tasks*. The **Claude Code** product (a CLI and IDE plugin) is specifically aimed at software developers. In Claude Code mode, chat messages might include code context, outputs, and developer instructions. Large code files, diffs, or logs can be fed to Claude, which can rapidly consume tokens. For non-developers, Claude used via web is primarily Q&A and content generation similar to ChatGPT.

These design choices yield some distinctive usage patterns for Claude:

3.2 Session-Based Chat

Claude's paid plans have a session usage limit that resets every five hours and weekly usage limits that reset once a week ([Claude Help Center](#)). Track these on their respective reset schedules; starting or clearing a conversation is a context-management action, not a way to refill either allowance.

3.3 Token Drain in Claude Code

A salient pattern in Claude Code (the coding-focused mode) is that **each file or conversation snippet added to the chat context is persistent**. If a developer commands Claude to analyze their entire repository, reading through hundreds of source files, all of those tokens will live in memory going forward. Without careful management, this can burn through context. Harika Yenuga's case illustrates this: during a single debugging session, Claude Code had read many files and outputs until the context bar showed 94% capacity ([harikayenuga.medium.com](#)). At that point, Claude began forgetting details and repeating work, indicating that the conversation had become *too large and inefficient*. This mirrors ChatGPT's behavior with long chats, but with a coding flavor (reading large JSON outputs, lock files, etc).

Anthropic documents that Claude Code costs vary with model choice, codebase size and usage patterns ([current cost documentation](#)). Establish a baseline for the team's own workload before budgeting. For teams working across time zones and running long asynchronous sessions, actual consumption can spike (Branch8 reports up to \$14/day per developer in Vietnam due to compounding usage) ([branch8.com](#)). These numbers show that developer workflows – even more than casual chats – can drive massive token usage in Claude.

3.4 Wasted Token Patterns

Many of the same inefficiencies seen with ChatGPT recur with Claude, often exacerbated by familiarity biases:

- **Lingering Irrelevant Context:** Retained history can still incur token charges; eligible cached history is billed at the cached-token rate rather than fully reprocessed ([Anthropic's caching documentation](#)). For instance, Yenuga notes asking Claude to fix an unimportant issue repeatedly that had been dealt with 20 minutes earlier, because the model “forgot” amid the noise ([harikayenuga.medium.com](#)).
- **Unprocessed Documents:** Like ChatGPT users, some Claude users upload raw data (PDFs, spreadsheets) without preprocessing. Geeky Gadgets warns that “uploading raw files” is a common waste: instead, converting to Markdown or extracting the essence reduces token overhead ([www.geeky-gadgets.com](#)).
- **Over-Specification in Prompts:** Users often place all backstory or detailed instructions in the prompt, even if not necessary. Since Claude retains context, repeating information in every prompt is redundant.
- **Misuse of Model Power:** Running Claude Opus (the most expensive model) on trivial tasks is wasteful. Geeky suggests assigning “match models to tasks” – use cheaper models (e.g. Claude Sonnet or even Haiku) for simple tasks ([www.geeky-gadgets.com](#)).

3.5 Context Commands and Tools

Claude Code offers explicit commands to manage tokens that ChatGPT currently does not. These inbuilt tools shape usage patterns:

- **/clear:** This command resets the conversation, discarding all prior history. Yenuga calls it the “hard reset” ([harikayenuga.medium.com](#)). Using /clear between unrelated tasks is considered best practice to avoid context pollution. Indeed, Yenuga notes that although /clear itself costs about 20K tokens to run, it is *far less* than the cost of continuing with a bloated context ([harikayenuga.medium.com](#)).
- **/compact:** Claude Code can auto-compact or manually trigger compaction. Compaction summarizes and prunes older context to save space. The Anthropic docs note that Claude auto-compacts when context exceeds ~95% and users can also call /config to toggle it ([docs.anthropic.com](#)). Yenuga's workflow also uses a custom “compact.md” instruction to succinctly summarize the project state. This command effectively reduces token usage on the fly.
- **Persistent Files and File Access:** Claude Code allows a project-level memory file `CLAUDE.md` which is reloaded each session. Yenuga emphasizes keeping this file “lean” – only 1.5k tokens minimal – because everything in it is pre-consumed ([harikayenuga.medium.com](#)). A `.claudeignore` file has no effect in Claude Code. Use documented Read deny rules for file-tool access, such as `Read(./node_modules/**)`, in Claude Code settings ([permissions documentation](#)). Review the documented rule coverage before relying on these settings to control access.

- **Model Choice:** Claude Code's environment variables allow choosing between models (e.g. Haiku vs Sonnet vs Opus). By default, expensive models might be selected. Users often optimize by setting cheaper models (Haiku) for routine tasks and reserving Sonnet/Opus for core reasoning (harikayenuga.medium.com) (branch8.com). For instance, Elton Chan's team at Branch8 found replacing many sessions with Haiku (92% cheaper) did not hurt quality for mechanical tasks (branch8.com).

These tools shape how developers naturally control token growth. In ChatGPT, an analogous strategy would be manually restarting chats or switching models manually, but Claude provides built-in commands that make it explicit. The outcome is that savvy Claude users learn to *architect* their interactions (project structure, compact commands) to avert token waste.

3.6 Usage Caps and Policy

Claude's platform has been experimenting with per-user and per-session caps to handle demand. A notable recent change (Mar 2026) adjusted the 5-hour session allowances during peak hours (www.techradar.com). Anthropic's engineer Thariq Shihipar wrote:

"If you run token-intensive background jobs, shifting them to off-peak hours will stretch your session limits further... We know this was frustrating." (www.techradar.com).

This announcement acknowledging that about 7% of users would hit limits more frequently highlights how quickly one can exhaust session tokens. Anthropic's policy reminds users to "start thinking more strategically about when you use your Claude account" to avoid burning out allotted tokens (www.techradar.com). In effect, both ChatGPT and Claude are moving towards encouraging efficient usage: ChatGPT with ads and subscription limits (www.techradar.com) (www.tomshardware.com), Claude with time-window limits and explicit cost controls (www.techradar.com).

In summary, **Claude usage patterns** mirror ChatGPT in many respects (long contexts, hidden overhead), but with specific twists. The availability of context commands, the emphasis on structured workflows (especially in coding), and the evolving subscription quotas all influence how tokens are consumed. With these patterns in mind, we turn to **comparisons and differences** between the two systems.

4. Comparing ChatGPT and Claude Tokenization and Costs

4.1 Tokenization Differences

In practice, ChatGPT (GPT-3.5/4) and Claude tokenize text in broadly similar ways, but there are subtle distinctions:

- **Language Coverage:** Both are multilingual. Early GPT tokenizers were primarily optimized for English (with some support for other Latin and some non-Latin scripts). Claude's tokenizer, similarly, handles multiple languages. For OpenAI models, a rough English-text estimate is 0.75 words per token, or about 1.3 tokens per word; check specific strings with the relevant tokenizer rather than assuming a universal ratio ([OpenAI key concepts](#)). However, for most Western languages, the average token/word ratio is comparable.
- **Casing and Whitespace:** ChatGPT's BPE tokenization is case-sensitive and preserves punctuation. Claude's tokenization details are proprietary, but output comparisons suggest similar behavior. One practical difference: adding extra spaces or unusual punctuation can increase token count. For example, GPT splits "COVID-19" into multiple tokens. In general, both models will count each punctuation mark and numeric digit as separate tokens if not part of an existing token. For optimization, it's often recommended to remove needless whitespace or combine words (e.g. avoid sending overly verbose system prompts).
- **Code vs Text:** When dealing with code, token counts can differ. GPT tokenization is wordpiece-based even for code (e.g. "functionName()" may split into ["function", "Name", "()", ...]). Claude's behavior with code can vary, especially in Claude Code mode, but everything is ultimately broken into tokens similarly. Developers often find that a few lines of code can cost dozens of tokens if not formatted or summarized. There are no dramatic differences in token accounting between the two models on pure text inputs, so optimization advice (be brief, remove filler) transfers across.

Overall, **no major departures in tokenization render** one model infeasible compared to the other in terms of optimization. Both count things like punctuation, newlines, and spaces. So techniques like chunking text at sentence or paragraph level work for both, and advice to "explain less and show code, not words" applies universally. The following sections will therefore treat token basics similarly for ChatGPT and Claude, delving instead into differences in context handling and pricing.

4.2 Pricing and Cost Structure

Table 1 compares API text-token prices **per million input tokens** and **per million output tokens**, with separate rates for each model ([OpenAI API pricing](#); [Anthropic API pricing](#)). Use model-specific input and output rates when estimating API costs; assess consumer subscription allowances separately.

- **Subscription vs Pay-as-you-go:** ChatGPT (consumer) tends to be flat-rate *per-user* (with heavy subsidies) and per-token *on the enterprise API*. Claude's pricing is largely per-token for commercial use (www.madrona.com), except for included quota on Pro/Max tiers. In essence, heavy API usage on either platform is billed similarly.
- **Usage Limits:** ChatGPT Plus usage limits can vary with system conditions ([OpenAI Help Center](#)). For Claude, track five-hour and weekly allowances on the separate schedules described in Section 3.2. Do not use advertising or a conversation reset as a proxy for the applicable allowance.

- **"Auto-Compact" vs Manual Summarization:** Claude Code can auto-compact when reaching ~95% of its context window; the ChatGPT app offers no equivalent user-facing compaction command. This is an architectural advantage in token efficiency, albeit hidden from user control (docs.anthropic.com).
- **Background Token Consumption:** Claude Code's background processes can consume tokens even without active interaction, typically costing under \$0.04 per session ([Anthropic's cost documentation](#)).

In summary, **none of the strategies below assumes one model is cheaper by orders of magnitude**; both require vigilance. It is instructive, however, to benchmark tasks on both systems. Some reports (e.g. Tom's Guide comparisons) suggest Claude often yields more detailed replies but may use more tokens; ChatGPT might be more concise but slower to load. In any case, *token efficiency* techniques (see Section 5) generally apply to both. Organizations often keep both models available and direct different queries to each resource depending on needed depth vs cost tolerance.

4.3 Context Windows and Long-Form Use

The **context window** size is a key operational difference. As of 2026, leading models are offering extremely large context capabilities:

- OpenAI's high-end GPT-4o model supports up to 128,000 tokens (gptbreeze.io). Claude Opus 4.6 and Sonnet 4.6 include 1,000,000-token context at standard pricing on the Claude Platform ([Anthropic](#)). Large windows can accommodate lengthy material; measure the task's accuracy and actual token charges rather than inferring a quadratic bill from attention complexity.
- Even at "only" 8,000–32,000 token limits, ChatGPT can handle substantial text (e.g. full reports or long code diffs). A 32k token conversation is roughly 24,000 words – a multilayered analysis. Once these windows are exceeded, both ChatGPT and Claude will truncate older content, potentially losing context. Useful optimization: when context is near capacity, use `/compact` (Claude) or start a new chat (ChatGPT) to frame only the relevant bits.
- **Memory Overhead:** It is also critical to note the hidden costs of very large context: even if a model advertises a 1M token input, the actual usable effective context might be much smaller. As one analysis notes, LLMs often struggle to utilize the full window coherently – memory "vanishes" in the middle of too-long prompts (www.tomsguide.com). Thus, for both ChatGPT and Claude, chunking large inputs (e.g. dividing a novel into sequential conversational steps) can be more effective than a single massive prompt.

In sum, while ChatGPT and Claude are expanding their context limits, the lesson persists: token cost accumulates with context length, and longer context can paradoxically reduce model accuracy. The following sections focus on how to engineer prompts and workflows given these realities.

5. Token Optimization Techniques

With awareness of token challenges, we now survey **concrete optimization techniques** for ChatGPT and Claude. Many strategies apply to both systems, while some are specific to Claude Code's features. We categorize them into (i) prompt formulation, (ii) context management, and (iii) system-level workflow strategies.

5.1 Prompt Formulation and Compression

5.1.1 Concise and Clear Prompts

The most basic tactic is simply to **be concise**. IBM Developer assigns a sample prompt 25 instruction tokens and a cost of \$0.025 ([IBM Developer](#)), implying \$0.001 per instruction token. These illustrative figures do not establish measured end-to-end savings or equivalent answer quality; measure both for your workload. Similarly, adding extraneous adjectives or overly polite phrasing can add multiple tokens with little semantic gain. Users should avoid filler phrases: e.g. instead of "Could you please summarize the following text for me?", simply say "Summarize the following:".

Table 2 shows example prompts before and after optimization (from IBM's blog):

Strategy	Original Prompt	Optimized Prompt	Tokens (orig)	Tokens (opt)	Cost (orig)	Cost (opt)
<i>Trimming verbosity</i>	"Please provide a detailed summary of the customer's purchase history, including all items purchased, dates of purchase, and total amounts spent." (medium.com)	"Summarize the customer's purchase history." (medium.com)	25	7	\$0.025	\$0.007
<i>Semantic chunking</i>	Same detailed prompt as above (medium.com)	Split into two prompts sent sequentially: 1. "Summarize the customer's purchase history." (7 tokens) 2. "Include items purchased, dates, and total amount." (10 tokens) (medium.com)	25 (instruction text)	17 (combined instruction text only)	\$0.025 (illustrative instruction-only cost)	Not established for two sequential requests

Table 2. Illustrative instruction-text examples from IBM Developer; the dollar figures assume \$0.001 per instruction token and are not actual API prices. The two chunked instructions are listed as 7 + 10 = 17 tokens; that is their combined text length, not the total usage of two conversational requests. A full cost comparison must include retained history with its cache treatment and generated responses ([Anthropic's cost explanation](#)). Measure answer quality and end-to-end usage before claiming equivalent results or overall savings.

The key principle is to turn any prompt into a *direct instruction with minimal words*. Avoid polite preambles ("Could you please", "I want you to..."), redundant adjectives ("detailed", "comprehensive" unless needed), and meta-comments ("By the way, I have an upcoming test..."). Users should carefully state exactly what's needed

and nothing more. In cases where a lot of context is needed, see below on chunking and summarization.

5.1.2 Controlled Generation Length

For ChatGPT/OpenAI API users, specifying a maximum response length can prevent runaway outputs. For instance, setting `max_tokens` to a reasonable cap (in a technical answer required token limit) ensures the model stops when the user's need is met. In Claude Code, use the `CLAUDE_CODE_MAX_OUTPUT_TOKENS` environment variable, for example `CLAUDE_CODE_MAX_OUTPUT_TOKENS=4096 claude`, to limit output tokens for most requests ([environment variables](#)). This differs from `--max-turns`, which limits agentic turns in print mode ([CLI reference](#)). This prevents paying for excessively verbose answers. In practice, one might request "List the top 5 X" instead of "Give as much information as possible about X." By bounding length, you avoid the flood of tokens for small returns.

5.1.3 Semantic Chunking and Summarization

A more advanced prompt strategy is **chunking**: breaking a large request into semantically coherent pieces. Table 2 lists 25 versus 17 as illustrative instruction-text counts, not the total cost of one request versus two conversational requests. Anthropic's [cost explanation](#) includes cached history, new input and output in the per-turn bill. When summarizing a long document in chunks, measure all requests and generated summaries before claiming overall savings or better comprehension.

Recent research formalizes this. The "SCOPE" approach (Zhang et al. 2025) uses a generative summarization model to compress prompts. It splits the original context into semantic chunks, assesses relevance, then rewrites each chunk concisely with another model ([arxiv.org](#)). This yields a significantly shorter prompt with minimal loss of information, outperforming naive token-removal methods. In practice, an engineer might manually apply a version of this: e.g. summarize long text with ChatGPT itself ("Summarize the previous section in 50 words") before feeding it back to Claude for deeper analysis.

While promising, such compression methods must be used carefully. If consequential details are inadvertently omitted, model performance suffers. Thus, chunking is most effective when followed by checks: e.g. verify that the summary captures all required points, or use techniques like bullet lists (which grant structure without extra tokens).

5.1.4 Prompt Pre-Processing

Some scenarios allow **external pre-processing** to save tokens. For example, instead of entering raw data, one can filter or tokenize offline. Large tables or logs can be pruned of irrelevant columns or rows beforehand. Similarly, documents might be converted to succinct notes: Geeky Gadgets specifically recommends converting PDF or Word docs into Markdown because markup is token-efficient ([www.geeky-gadgets.com](#)). For example, the phrase "**bold text**" in Markdown might count as fewer total tokens than a PDF so foreign to the model. Another trick: use in-system variables or anchors. Claude Code supports "labels" (e.g. referencing a baseline document by ID instead of re-sending its content every time).

Furthermore, some tasks can be reframed to require fewer tokens. If you just need a one-line answer, ask directly. If the model should operate over data, consider instructing it to "examine variable X" rather than sending the variable's entire contents.

In summary, prompt-level optimizations revolve around eliminating unnecessary verbosity, decomposing complex requests, and pre-processing data **before** it becomes tokens. These steps ensure the prompt itself is as token-efficient as possible. However, they address only the **front-end tokens**; we must also manage the **back-end (history) tokens**. The next section covers that.

5.2 Context Management

5.2.1 Starting Fresh: Conversation Resets

A useful context-management tactic is to **reset the conversation** when switching to unrelated work ([Yenuga's account](#)). In ChatGPT, this means deleting or closing the chat and starting a new one. In Claude Code, use the `/clear` command.

This may seem counterintuitive — after all, we often like longer chats to maintain coherence. However, if you have changed topics or solved a problem, carrying all prior text only burdens future messages. Yenuga notes that `/clear` “costs about 20K tokens to restart... (but) that’s nothing compared to the quality loss from a polluted context window” ([harikayenuga.medium.com](#)). In her experience, strategic use of `/clear` between distinct tasks significantly extended session productivity. Geeky Gadgets similarly advises resetting after **10–15 turns** to prevent drift ([www.geeky-gadgets.com](#)). In empirical terms, this can reduce *invisible* tokens dramatically — you avoid re-sending 10+ past messages (often thousands of tokens) with every new user query.

Before resetting solely to reduce costs, check whether a shared prefix already benefits from **OpenAI prompt caching**. Reusing that prefix can avoid repeating its computation.

Where resets are infeasible (e.g. you need some ongoing history), consider manual compaction: ask the model to summarize past conversation into a single message, then clear everything before that message ([harikayenuga.medium.com](#)). Claude’s `/compact` or `/force-compact` can assist: for instance, `SLASH /compact focus on problem X - summarize relevant points`. This actively condenses history. Even automated, Claude Code can be set to auto-compact near limits ([docs.anthropic.com](#)), though custom instructions can make it more efficient (e.g. focus only on code changes).

Resetting is one context-management option. Claude Code also automatically compacts conversations before the context window fills ([Anthropic best practices](#)), so a reset is not the sole remedy for growing history.

5.2.2 Context Anchoring and Memory Files

Both systems allow a form of *anchoring critical context* outside of the normal dialogue stream. ChatGPT has the concept of *system prompts* (hidden to users) and Claude has `CLAUDE.md` (visible to users). For Claude Code, this `CLAUDE.md` serves as a persistent memory of project info that loads each session ([harikayenuga.medium.com](#)). The trick is to keep this anchor file extremely concise: it must contain only the most essential stable facts (project overview, style rules, tech stack), because every token there is paid every session. Yenuga illustrates a lean file with separate upper bounds of under 200 words and under 1,500 tokens, covering exactly the project’s tech stack and a few key rules ([harikayenuga.medium.com](#)). This minimized approach ensures continuity (Claude “remembers” the project basics) without burning tokens on stuff he can just paste or recall.

Similarly, for ChatGPT one can simulate an anchor by always including (in the first user message) a succinct summary of important constants, or by pinning a “system prompt” via the API. In practice, one might store static project data in an external file and only paste in the relevant bits when needed, rather than retyping everything each chat.

Another anchoring hack is *offloading to retrieval tools*. For example, instead of embedding a whole knowledgebase in conversation, one might use ChatGPT plugins or Claude's retrieval tools (if available) to fetch info on-demand. This shifts tokens away from the model and to an external search, which may be cheaper or pre-paid. If an LLM can call an API or look up a database, the conversation can simply include a brief instruction with the query rather than the full content.

5.2.3 Focused Prompting

When continuing a conversation, one should **focus prompts on new information**. Treat the model like a person with short-term memory: only remind it of what it has “forgotten”. If, for example, your ChatGPT discussion is about planning a trip and you switch to asking for visa requirements, re-state the relevant destination (otherwise the AI may not recall it ten turns later). But do not re-paste all previous dialogue unnecessarily. In practice, we advise explicitly anchoring the question to specific context:

“Regarding [Topic/Situation already established], answer [new question].”

This cues the model without re-embedding whole paragraphs. It ensures the model knows *which part of the memory to use*.

5.2.4 Semantic Scope Scoping

Both IBM and Anthropic emphasize the importance of scoping context. Anthropic's docs advise feeding *only relevant information* to the model ([medium.com](https://medium.com/@anthropic/docs)) (docs.anthropic.com). This means pre-cleansing input: removing irrelevant sentences, focusing on key facts, using bullet points, etc. For example, if a prompt involves analyzing a document, first remove sections that aren't needed for the analysis (e.g. appendices, legal disclaimers, verbose explanation) and give the model a trimmed version. This targeted approach was shown to minimize token usage while preserving answer quality ([medium.com](https://medium.com/@anthropic/docs)).

Another IBM suggestion: use **format tricks** like bullet lists, tables, or code blocks to convey structured info compactly. A well-formatted list can often compress description vs. narrative text. For instance, instead of one long prose chunk describing multi-part requirements, use enumerated points. The transformer parses structure efficiently, often saving tokens.

5.2.5 Model Selection and Purpose Matching

To minimize tokens, one can choose an LLM whose “bias” allows brevity. For instance, instruct ChatGPT: “Answer in bullet points” or “Please answer succinctly”. Some models excel at brevity if asked. Do not select GPT-3.5 Turbo for a new workflow: OpenAI shut it down on October 23, 2026, and it is no longer available in the API ([OpenAI model documentation](https://openai.com/blog/gpt-3-5-turbo)). Evaluate currently available models against your task's quality and

cost requirements. The Branch8 case study echoes this: “*Focus sessions cost 67% less than open-ended mega-sessions,*” implying that planning out concise sub-tasks yields far fewer tokens than letting a model ramble (branch8.com).

In Claude’s ecosystem, Anthropic offers specialized models (Haiku/Sonnet/Opus). Use Haiku (the cheapest) by default for simple tasks (paraphrasing, short Q&A) and escalate to Sonnet/Opus only when needed (branch8.com) (harikayenuga.medium.com). This way, expensive tokens are only spent on the hardest problems. One user sets `CLAUDE_CODE_SUBAGENT_MODEL=haiku` for routine tasks, reserving Opus for complex reasoning (harikayenuga.medium.com). This gradation minimizes token expenditure for easy questions.

5.3 System-Level and Workflow Strategies

5.3.1 Caching and Memoization

An organizational approach is to **cache results** of frequent queries outside the model. If the same question arises multiple times (e.g. “What does this function do?” with the same code snippet), store its answer locally rather than re-ask the LLM. Claude Code also auto-compacts long conversations so that less history is resent (docs.anthropic.com). OpenAI provides a discounted “cached input” price for repeated prompt prefixes (platform.openai.com). Thus, you should architect your application to reuse identical prompts. For instance, prefix your prompts with a unique hash; if the same prompt reappears, use the previous answer.

5.3.2 Rate Limits and Throughput

At a larger scope, teams can set **token budgets and monitoring**. Branch8 instituted team dashboards to flag users burning tokens unusually fast (branch8.com). We recommend exposing token usage to end-users: e.g. after each ChatGPT exchange, show how many tokens were used. Awareness itself often curbs wasteful behavior. Administrators can enforce hard caps or slowdown above thresholds. For example, require manual intervention if a user exceeds a certain tokens-per-day; or throttle queries if no context-clearing has occurred for a long period.

5.3.3 Automated Context Guards

Some advanced implementations wrap the LLM with a system that checks token use. For instance, before sending a query, compute projected total tokens if context were added. If above a threshold, automatically insert a “/clear” or rewrite the prompt to be more compact. Tools exist (third-party or built-in) to measure token consumption progressively. For example, proxy libraries such as LiteLLM tally usage per request. Using such tools, one can trigger warnings when context is bloated and recommend action.

5.3.4 Content Format Optimization

An often-overlooked strategy is choosing the *right response format* to save tokens. For example, JSON outputs or structured data can be more compact than free text when applicable. If you only need data (e.g. list of name-value pairs), instruct the model to output JSON; it typically omits natural language fluff. Embedding an answer in code fences or markdown can make it shorter per information. There is no citation here, but it’s a practical tip many practitioners use.

5.3.5 Disabling Unnecessary Features

Administrators can disable optional prompt suggestions across an organization by setting `promptSuggestionEnabled` to `false` in managed settings ([Anthropic's interactive-mode documentation](#)). Also, avoid enabling tools (like web browsing) unless needed, as each tool's schema may swallow tokens in the background. Audit any bots/plugins that feed data to the model inadvertently. The Geeky Gadgets list advises “audit plugins and connectors – identify and remove tools that consume tokens unnecessarily” (www.geeky-gadgets.com). This is akin to pruning the application's integration to only essentials.

5.4 Case Study Highlights

The above techniques are not just theoretical. Three real-world examples demonstrate their impact:

- **IBM Prompt Rewriting:** IBM Developer recommends refining prompts based on model outputs and user feedback. Apply that advice to Table 2: measure usage and answer quality in your own workload before treating a shorter instruction as an equivalent, cheaper result ([IBM Developer](#)).
- **Claude Code Workflow Overhaul:** Harika Yenuga (2026) describes a personal case: after burning ~200K tokens in 20 minutes on a defective prompt structure, she redesigned her project with strict rules (lean `CLAUDE.md`, frequent `/clear` usage) and “smart session hooks”; her `.claudeignore` recommendation is ineffective because that file has no effect in Claude Code ([permissions documentation](#)) (harikayenuga.medium.com). The result was a **70% reduction** in token use and far longer effective sessions in a Claude Code debugging workflow (harikayenuga.medium.com). Her principles are broadly applicable: minimize permanent context, isolate code reading to on-demand docs, and let the model learn iteratively (by writing corrections into memory).
- **Team Budgeting (Branch8):** At Branch8, a cross-country dev team was running a \$2,400 monthly Claude bill. By introducing **token budgets, per-request caching, and segmenting workflows** over 8 weeks, they cut it to \$680 (72% less) (branch8.com). Key tactics included splitting large tasks into smaller runs (focused sessions cost ~67% less (branch8.com)) and automatically caching stable context chunks (prompt caching saved ~90% of those token costs on Sonnet) (branch8.com). They also leveraged cheaper models for repetitive tasks (their note: using Haiku was 92% cheaper than Sonnet with no loss in output quality (branch8.com)). This shows that organizational policies (training devs, setting quotas, adjusting the tech stack) can yield large token efficiencies.

These case studies reinforce that **process and discipline** matter as much as prompting skill. The “hidden tax” on token usage can be tamed significantly by structural changes to how teams and users interact with models.

6. Data Analysis and Examples

This section compiles quantitative data and examples illustrating token dynamics.

6.1 Quantifying Progressive Costs

Table 3 is a simplified cumulative input-text example: request k contains k equal-sized units of retained input, with no trimming or compaction. It counts repeated text across requests, rather than measuring computation or billed cost.

Message #	Independent Inputs (units)	Cumulative Retained Input (units = $\sum 1..n$)	Input-Text Ratio
10	10	55	5.5×
25	25	325	13.0×
50	50	1275	25.5×
100	100	5050	50.5×
200	200	20,100	100.5×

Table 3. Under the stated assumptions, cumulative retained input is $n(n+1)/2$ units, compared with n independent one-unit inputs. These are input-text counts, not observed costs.

At request 50, retained input is 50 units; the cumulative total is 1,275 units, or 25.5 times 50 independent one-unit inputs. Only an uncached, untrimmed, input-only comparison at a constant input rate would translate those ratios directly into input charges. They do not establish ratios for total bills, which also include generated output. Anthropic describes Claude Code's per-turn bill as cached-history reads, new input and output ([cost explanation](#)). Claude Code automatically compacts long conversations before the context window fills ([best practices](#)). Account for cache-read and cache-write rates, output and compaction when estimating actual costs.

6.2 ChatGPT Usage Statistics

External data underline the scale of ChatGPT usage:

- **Daily Tokens:** According to OpenRouter (via TechRadar), OpenAI models recorded ~78.3 billion tokens on OpenRouter on Sep 18, 2025, the highest since the summer slowdown (www.techradar.com). Of this, GPT-4.1 Mini accounted for ~26.9B tokens. This implies extreme concurrency and breadth of use. Even with a subsidized cost, handling 78B tokens/day (billions of GPU operations) is staggering.
- **User Base:** OpenAI reports ChatGPT has “hundreds of millions of users” (www.techradar.com). Even if the median user sends only 100 tokens/day, the aggregate easily reaches billions of tokens. TechRadar notes that subscription income covers only a small slice of the cost of serving these users (www.techradar.com) reflects this scale. For education/enterprise planning, one must expect very high usage rates given these baselines.
- **Polite Phrases:** Tom's Hardware cites Altman that polite replies to users (“thanks”, “you're welcome”) alone use *tens of millions of dollars* for OpenAI (www.tomshardware.com). This emphasizes that even tokens normally considered “free fluff” accrue significant real-world bills.

These numbers serve as a reminder: **ChatGPT clients must assume that tokens equate directly to resource usage at massive scale.** Each optimization of prompt or session yields not just minor friction improvements, but potentially millions of dollars saved when scaled across all users.

6.3 Case Example: System Prompt Overhead

For Claude Code, inspect the context in your own session with `/context` to see what is consuming space ([Claude Code documentation](#)). Use that inspection to identify unnecessary context rather than treating an anecdotal estimate as a universal 5,000-token minimum.

6.4 Branch8 Team Example

To quantify savings, consider Branch8's optimization after adopting Claude Code in early 2025: its 6-person team spent \$2,400 in the first month. Within eight weeks of implementing optimizations (caching, budgets, model switching), spend was \$680 – a 72% drop ([branch8.com](#)). During this period, output quality remained consistent. They attribute most gains to two factors: *prompt caching* (avoiding reprocessing repeated inputs, saving ~90% of those tokens) and *session focus* (keeping conversations narrow, cutting costs to ~33% of open-ended sessions ([branch8.com](#))).

This real-world ROI illustrates the Pareto principle: a few high-leverage changes (caching, context resets, model matching) cut bills by roughly 72% without altering output goals. It underscores that **data-driven token monitoring** and **team-level policies** are as vital as individual \$/token considerations.

7. Case Studies and Real-World Examples

In practice, many organizations and users have publicly shared their strategies for token optimization. We highlight a few prominent examples as “case studies”:

- **IBM Developer (Prompt Engineering Best Practices):** In a 2024 IBM Developer article, Supal Chowdhury presents a litany of prompt optimization heuristics. Key advice includes: “*unambiguous, brief instructions*”, “*provide context concisely*”, “*use examples (few-shot) sparingly*”, and *always count tokens to stay within limits* ([medium.com](#)). The article's worked example (Table 2 above) shows the tangible benefits of even small prompt edits. IBM also recommends “effective chunking”: splitting tasks into multiple mini-prompts ([medium.com](#)), which not only saves tokens but often yields higher-quality focused responses. This reflects IBM's internal emphasis on prompt engineering as a first-order practice in AI product development.
- **Harika Yenuga (Developer Productivity with Claude Code):** In April 2026, developer Harika Yenuga authored a detailed blog about her firsthand experience cutting Claude Code token usage. Her key takeaway was that “**the context window is your most important resource to manage**” ([harikayenuga.medium.com](#)). She reorganized her Claude project with strict conventions (minimal startup memory file, a `.claudeignore` intended to exclude `node_modules` and other huge directories, although that file has no effect in Claude Code ([permissions documentation](#)), constant use of `/clear` and `/compact` commands) and trained Claude iteratively by correcting it (adding mistakes to

CLAUDE.md so they become preset knowledge) (harikayenuga.medium.com). The result was a 70% *reduction in tokens* for equivalent work (harikayenuga.medium.com). She presents her folder structure in the blog (rooted by CLAUDE .md, annotated with project rules). This case exemplifies how **developer workflow discipline**, not just prompt words, can save enormous tokens in a code-centric workflow.

- **Branch8 – APAC Dev Team (Workflow Engineering):** As noted, Branch8’s 2026 article describes implementing Claude Code across Hong Kong, Singapore, Vietnam, and the Philippines (branch8.com). Their multi-faceted approach serves as a blueprint for any dev team:
 1. **Token Budgeting:** They set explicit per-user and per-project token budgets and tracked use.
 2. **Prompt Caching:** They deployed caching for common operations (e.g. architectural summaries), so the model rarely reprocessed identical prompts (saving ~90% on those).
 3. **Modular Sessions:** They broke large tickets/projects into short “sprints” of conversation, covering only one feature at a time (focused sessions). This made each 5–10-message interaction much cheaper (67% less cost vs previous approach (branch8.com)).
 4. **Model Triage:** Simple tasks (writing tests, refactoring suggestions) were delegated to Haiku; Opus/Sonnet were reserved for core logical reasoning.
 5. **Monitoring and Dashboards:** They used weekly team dashboards to surface cost outliers before they compounded.

Within two months, they stabilized a 72% cost reduction (branch8.com). Importantly, their output (code quality, velocity) did not suffer.

- **Online Forum Tips:** Developers also share insights on forums (StackOverflow, Twitter threads). Common tips include:
 - “When ChatGPT goes off on a tangent, type Stop or regenerate.” (Long hallucinations mean extra output tokens.)
 - “Use limit: phrases” – e.g. “Give the answer in no more than 100 words.” This is not always obeyed fully but can curb runaway answers.
 - “For Claude, /cost often surprises you – run it to see your actual spend per session.” Actually, Claude Code’s CLI /cost (for developers) shows token usage statistics for the current session (docs.anthropic.com).
 - “Use system messages where possible.” (Developers embed instructions as “system” content to avoid re-sending them each turn, via the API.)

These case studies demonstrate practical impact: teams and individuals routinely **halved or better** their token consumption by following best practices. While expert prompting can yield modest gains, the biggest returns often come from workflow and tooling changes as illustrated above.

8. Implications and Future Directions

The technical and economic landscape of LLMs continues evolving, which has important implications for token usage:

8.1 Larger Contexts – Double-Edged Sword

Emerging LLMs are increasing context lengths dramatically (100K+ tokens as noted). This theoretically allows single-query processing of massive documents or codebases. However, as technology analyst Tom's Guide observed, Anthropic's 1,000,000-token context "translates to half a million words" but "AI can't usually handle incredibly long prompts" (www.tomsguide.com). Research suggests attention mechanisms become overwhelmed with very long inputs, and practical response quality degrades. Additionally, using longer contexts without trimming frees no CPU/IO – it just piles up more tokens to process.

Going forward, we expect:

- **Targeted Autonomization:** Instead of tossing 1M tokens at once, users will need to employ tool-kits (retrieval, iterative processing, memory banks) so that an LLM only loads what is relevant for each step. Tools like LangChain and Claude's retrieval will become more important routes than raw context.
- **Sublinear Attention Models:** If / when transformer variants with more efficient (e.g. sparse or linear) attention become available, they may allow larger effective context without quadratic cost. This would dramatically reduce the hidden tax. Some open-weight models (for example Llama 4 Scout) advertise context windows of up to 10M tokens (www.tomsguide.com). Adoption of those could diminish token costs (though they often have weaker performances otherwise).
- **Composable Memories:** Next-generation chat interfaces may incorporate persistent memory differently. For instance, instead of replaying raw text, the model might index context into embeddings, or use learned memory networks. Early investigations (e.g. Retrieval-Augmented Generation) do this. This could mean historical conversation consumes far fewer tokens (just relevant memories retrieved). Such architectures remain research topics, but they underscore the future: we may not have to prompt-engineer ourselves out of quadratic cost if the models internalize memory.

8.2 Pricing and Market Dynamics

The token optimization strategies here were partly driven by pricing structures. As OpenAI and Anthropic adjust pricing, user behavior will adapt:

- **Shift from "Freemium" to "Pay-per-Use":** We have seen hints of this. OpenAI is exploring advertising and usage quotas on ChatGPT to nudge users from "all-you-can-eat" toward more paid usage (www.techradar.com). Anthropic is explicitly "ending the all-you-can-eat era" by disallowing third-party unlimited usage and enforcing API billing (www.madrone.com). Over time, expect fewer flat-rate usage allowances, making token efficiency not just good practice but actually required to stay within budgets.
- **Model Proliferation:** As new models (GPT-5, Claude Sonnet 5.0, etc.) arrive, organizations will have more options. Some trend toward multi-model systems: cheap local models for filler tasks, and expensive clouds for necessity. We predict that intelligent multi-model orchestration (as suggested in Madrona: "hierarchical delegation") will be a mainstream engineering consideration (www.madrone.com).
- **Third-Party Tools:** Official tools like Claude's /compact or new ChatGPT plugins may emerge to automatically manage tokens. In the meantime, a cottage industry of token-optimizing utilities is likely to grow (e.g. community prompt compressors, token monitors). The market may even see services that

live in front of ChatGPT/Claude to trim prompts in real time.

8.3 Open-Source and Local Innovation

As noted in Madrona's analysis, a surge of open-source models with efficient architectures (Gemma 4, Qwen 3.5, GLM-5, etc.) is happening (www.madrona.com). Many of these boast massive contexts but are cheaper to run on local hardware. A savvy organization might offload certain tasks to local open models — effectively nipping tokens that would otherwise hit ChatGPT or Claude. For example, simple summarization tasks could be sent to an open-weight model such as Llama 4 on in-house GPUs, reserving ChatGPT strictly for high-value reasoning. This leads to a *hybrid strategy*: combination of open and closed LLMs to minimize overall paid tokens.

8.4 Token-Efficient Prompting Research

The field of **efficient LLM prompting** is maturing. We saw one example (SCOPE summarization) (arxiv.org), and there are others in lit (e.g. "LongChain" for progressive summarization, etc.). Expect more techniques whereby the model *learns to compress input on the fly* or is given a meta-prompt to economize tokens. For instance, in 2026 one could imagine new LLM features: a built-in tokenizer-aware summarizer, or native "trim" instructions. Researchers are also exploring continuous prompts (trainable token sequences) that convey constant instructions without repeating static text. These innovations could alter token patterns significantly once they settle. Our analysis should therefore be revisited as these methods enter adoption.

8.5 Ethical and User-Experience Considerations

Optimizing tokens has a trade-off: brevity vs. clarity. Excessive truncation can harm output quality or factual completeness. For example, pressuring a model to answer within 100 tokens may cut off nuance. System designers must weigh these factors. Best practices include ensuring prompts remain unambiguous even as they shrink, and possibly post-verification of trimmed answers.

Another implication: if everyone starts paring down prompts to tokens (like automated compaction), conversational AI experience may become more terse. This might frustrate casual users accustomed to "chatty" AI. There will need to be either educational cues ("Optimize prompts for cost and speed") or intelligent user interfaces that hide the complexity (as ChatGPT does by default).

Finally, transparency is key. Many users do not initially realize that LLM tokens cost money and resources (medium.com). There is a role for providing token-price feedback (e.g. "This request will use ~500 tokens") to help users make informed choices. OpenAI's persistent practice of showing upgrade/limit warnings is a nod in this direction, and Claude's `/cost` command is another. Ensuring users of both platforms have visibility into tokens and cost will shape the token usage culture.

9. Conclusion

As ChatGPT and Claude become deeply integrated into workflows, **token management** emerges as a foundational skill for AI practitioners. This report has shown that token usage is not merely a technical detail but a major driver of cost and performance. We have surveyed *token usage patterns* in these systems – from the quadratic blowup of multi-turn chats (medium.com), to the hidden overhead of system prompts (medium.com), to the daily churn of billions of tokens by global user bases (www.techradar.com).

Against this backdrop, we have provided a thorough set of optimization techniques. Brevity in prompt design, semantic chunking, conversation resets, and model selection all contribute to substantial savings (medium.com) (harikayenuga.medium.com). Contextual tools (like Claude's `/clear` and `CLAUDE.md`) serve as powerful levers. Case studies confirm that these are not theoretical: companies have slashed their LLM bills by over 70% via these methods (branch8.com) (harikayenuga.medium.com).

We also recognize the broader implications: as AI platforms tighten pricing (end of free lunch) and context windows grow, the incentives to optimize will only strengthen (www.madrona.com) (www.tomsguide.com). Innovations in model architecture and open-source alternatives will offer new avenues for efficiency, but the core relationship between tokens and cost will remain.

In closing, token-aware engineering is akin to resource-aware computing in earlier eras. Just as programmers once had to worry about CPU cycles and memory, AI developers now must worry about token cycles. Armed with the insights and techniques in this report, professionals can ensure that their use of ChatGPT, Claude, or any similar LLM is **scalable, cost-effective, and sustainable**.

References (selected): Authoritative sources are cited throughout. For example, IBM's developer blog on prompt engineering (medium.com), Anthropic's documentation (docs.anthropic.com), TechRadar and Tom's Hardware articles (www.techradar.com) (www.tomshardware.com), and the Madrona and Branch8 analyses (www.madrona.com) (branch8.com). All quantitative claims and recommendations above are supported by the literature and data from these sources. (Full inline citations provided in text.)

Source links

Links cited in this article, in order of first appearance. Full addresses are provided for readers using extracted text.

1. <https://medium.com/%4085.pac/the-ai-cost-curve-nobodys-talking-about-53e8071150c8>
2. <https://www.geeky-gadgets.com?p=489163>
3. <https://www.tomshardware.com/tech-industry/artificial-intelligence/openai-spends-millions-to-process-polite-phrases-such-as-thank-you-and-please-with-chatgpt>
4. <https://developers.openai.com/api/docs/guides/prompt-caching>
5. <https://www.techradar.com/pro/chatgpt-registers-huge-surge-in-traffic-as-schools-and-classes-resume-chatgpt-4-1-mini-helps-openai-to-record-highs-as-daily-token-generation-reach-a-staggering-78-billion>
6. <https://code.claude.com/docs/en/costs>
7. <https://medium.com/@85.pac/the-ai-cost-curve-nobodys-talking-about-53e8071150c8>
8. <https://medium.com/%40IBMDDeveloper/token-optimization-the-backbone-of-effective-prompt-engineering-65aad3f505f4>

9. <https://code.claude.com/docs/en/permissions>
10. <https://medium.com/@IBMDDeveloper/token-optimization-the-backbone-of-effective-prompt-engineering-65aad3f505f4>
11. <https://harikayenuga.medium.com/i-burned-through-200k-tokens-in-20-minutes-then-i-built-a-system-that-cut-it-by-70-c20713c895bc>
12. <https://gptbreeze.io/blog/gpt-4o-pricing-guide>
13. <https://claude.com/resources/articles/1m-context-ga>
14. <https://arxiv.org/abs/2508.15813>
15. <https://www.madrona.com/price-of-tokenmaxxing-claude-explosive-growth-cost-of-intelligence>
16. <https://www.linkedin.com/pulse/mastering-chatgpt-token-optimization-real-users-guide-nikolay-gul-a9hhe>
17. <https://platform.claude.com/docs/en/build-with-claude/prompt-caching>
18. <https://code.claude.com/docs/en/best-practices>
19. <https://www.techradar.com/ai-platforms-assistants/chatgpt/free-chatgpt-is-surprisingly-expensive-heres-why>
20. <https://openrouter.ai/docs/api/api-reference/datasets/daily-token-totals-for-top-50-models>
21. <https://www.techradar.com/ai-platforms-assistants/claude/claude-is-limiting-usage-more-aggressively-during-peak-hours-heres-what-changed>
22. <https://docs.anthropic.com/en/docs/claude-code/costs>
23. <https://branch8.com/posts/claude-code-token-limits-cost-optimization-apac-teams>
24. <https://platform.openai.com/docs/pricing>
25. <https://help.openai.com/en/articles/20001051-retiring-gpt-4o-and-other-chatgpt-models>
26. <https://help.openai.com/en/articles/6950777-what-is-chatgpt-plus>
27. <https://help.openai.com/en/articles/20001354-gpt-6-and-other-models-in-chatgpt>
28. <https://support.claude.com/en/articles/11049741-what-is-the-max-plan>
29. <https://support.claude.com/en/articles/11647753-how-do-usage-and-length-limits-work>
30. <https://code.claude.com/docs/en/prompt-caching>
31. <https://developers.openai.com/api/docs/concepts>
32. <https://developers.openai.com/api/docs/pricing>
33. <https://platform.claude.com/docs/en/about-claude/pricing>
34. <https://www.tomsguide.com/ai/anthropic-looks-to-beat-gpt-5-and-grok-4-with-this-one-major-upgrade>
35. <https://claude.com/resources/articles/maximizing-the-value-of-your-claude-code-sessions>
36. <https://code.claude.com/docs/en/env-vars>
37. <https://code.claude.com/docs/en/cli-reference>
38. <https://developers.openai.com/api/docs/models/gpt-3.5-turbo>
39. <https://code.claude.com/docs/en/interactive-mode>

THE PUBLISHER

About IntuitionLabs

IntuitionLabs is an AI consulting, custom software development and data engineering firm serving pharmaceutical, biotechnology, medical-device and other life-science organizations. We work with clinical, regulatory, medical-affairs, commercial, quality and IT teams to connect technology decisions with the work people need to accomplish.

AI consulting and adoption

Our AI enablement services cover readiness assessments, use-case selection, governance and policies, team workshops, adoption measurement and ongoing advisory support. We help organizations structure the information layer behind AI: source material, context, permissions and maintained knowledge that make generated answers useful and reviewable. Private LLM inference and hosted AI options support teams evaluating how to operate AI with appropriate control over their data and infrastructure.

Software, data and life-science workflows

IntuitionLabs develops custom software for pharma and biotech, integrates enterprise systems, and builds data engineering and business intelligence solutions. Areas of focus include AI agents, regulatory research, medical writing, medical affairs, CMC information, competitive intelligence and clinical-document workflows. Our eTMF intelligence work includes cross-system reconciliation and inspection-readiness support.

Enterprise platforms and regulated delivery

We provide Veeva services, application support, managed services, integrations and custom applications, alongside enterprise content work involving platforms such as Egnyte. For regulated workflows, our services include GxP enablement, computer-system validation and software development addressing 21 CFR Part 11 requirements. The applicable controls, validation responsibilities and acceptance criteria are defined for each engagement.

Work with IntuitionLabs

Explore [AI enablement](#), [pharma and biotech software development](#), [data engineering and BI](#), and [Veeva services](#). [Contact IntuitionLabs](#) to discuss your workflow, information sources and implementation needs.

IntuitionLabs publishes educational research to help life-science teams make informed technology decisions. Coverage of a product or organization does not imply a client relationship, endorsement or partnership.

Website: <https://intuitionlabs.ai>

This article is educational. Verify consequential medical, legal, financial, regulatory and technical decisions with appropriate professionals and the cited primary sources. Company services are described separately from the article's research findings.